

Crystal Racing Oil RSV-189 SAE 10W-60

A fully synthetic engine oil, designed for cars for race conditions

Product Description and Benefits

A fully synthetic engine oil based on carefully selected high quality synthetic base oils, all of which already have a natural, high viscosity index and which advanced and well balanced additives in order to obtain the following properties:

- a very low tendency to evaporation
- a high and very stable viscosity index
- a good resistance against shearing
- a high resistance against aging
- a safe lubrication film at low and very high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

Application

A fully synthetic engine oil, designed for cars for race conditions where the highest performance is required. This oil has proven its quality under the most extreme conditions particularly in races.

Crystal Racing Oil RSV-189 SAE 10W-60 meets the following performance specifications:

API SM/CF
ACEA A3/B4

Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/	0,867
Viscosity -25 °C	mPa.s	6040
Viscosity 40 °C	mm ² /s	155,10
Viscosity 100 °C	mm ² /s	24,20
Viscosity Index		189
Flash Point COC	°C	238
Pour Point	°C	-48
Total Base Number	mgKOH/g	9,7

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Crystal check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.